

RS DYNAMICS

Science for Homeland Safety

microRAMAN®

- the fastest
- the most accurate
- the smallest
- the lightest
- the most robust and reliable
- the easiest to operate

... pocket RAMAN SPECTROMETER - identifier



Detectable compounds:

- explosives
- narcotics
- chemical warfare
- pharmaceutical products
- hazardous material
- food materials (additives)

Specifications

microRAMAN®

» Technical parameters

Laser type: 785 nm semiconductor laser

Laser output power: Fully adjustable up to 470 mW

Detector type: Non-linear CMOS strip Spectral range: 200 - 2000 cm⁻¹ Spectral resolution: 12 cm⁻¹

Laser class: 3B

Detection/Identification time: typically 2 seconds Delayed Scan: 0 to (user defined) interval in seconds

Scan time: 2 - 20 seconds

Exposure: Automatic or manual with adjustable scan delay

Connectivity: WiFi, Bluetooth, USB 2.0 Data download: External Flash Drive

Optics: Interchangeable fix focus lenses adapters and vial

holder adapter

Screen: Color high resolution 6.5" touch screen

IP Protection: IP64 Weight: 650 g

Size: 225 x 109 x 38 mm

Battery: Li-lon, 8 - 10 hours operation for one charge External Power Supply: 110 - 240 V AC, 100 W (included)

Car charging adapter: CLA adapter (optional)
Operating temperature range: -15 to +55 °C
Storage temperature range: -25 to +55 °C
Robotic Applications: WiFi remote control
Consumables: No consumables required

Certification: CE. ROHS

» Features

- Identifies the widest spectrum of substances in solid and/or liquid form, including explosives, narcotics, chemical warfare agents, pharmaceutical products, hazardous materials and food additives, chem. residues
- More than 24 000 substances in the libraries
- Aditional manufacturer libraries available (Optional on request)
- Extension for new substances by customer supported
- Advanced mixture identification due to sophisticated determination algorithm
- Extremely user-friendly and intuitive operation via touch-screen
- Heavy-duty robust case designed for the hardest field/military conditions
- Robotic integration includes full remote wire-less operation
- Large colour display with self-explanatory graphic output

» Environmental

- No radioactive source inside
- No toxic materials inside, No toxic consumables (no consumables at all)
- Product fully environmentally recyclable at manufacturer site


>> Training


- No special operator's training and/or qualification required!
- » Various types of samples tested



» Application case







R5 DYNAMIC5[®] **LLC**

Technopark Zurich
Technoparkstrasse 1, 8005 Zurich
Switzerland
e-mail: info@rsdynamics.com
Internet: www.rsdynamics.com

RS DYNAMICS[®] Ltd.

Starochodovska 1359 CZ – 149 OO Prague 4 EU - Czech Republic e-mail: info@rsdynamics.com Internet: www.rsdynamics.com Locally distributed by: